XT-4015

Specification	XT-4015
Processor	Intel G1620 CPU, 2.7GHz / 2M Cache;
	Intel G2120 CPU, 3.1GHz / 3M Cache;
	Intel Core i3-3220 CPU, 3.3GHz / 3M Cache;
	Intel Core i5-3550s CPU, 3.7GHz / 6M Cache;
	Intel Core i7-3770 CPU, 3.9GHz / 8M Cache
System Memory	DDR3 1066/1333MHz, SO-DIMM socket x 2, max 16GB
Storage Device	SATA storage x 2; Factory default 500GB HDD x 1
Power Supply	12V DC power adaptor, 120W
OS Support	Windows 7/POSReady 7/Windows XP Pro/POSReady 2009/Windows Embedded 8.1 Industry / Linux per request
Connectivity	
LAN Port	10/100/1000Mb x 2
Serial Port	DB9 x 3 + RJ50 x 1 with 5V/12V support on COM1 / COM2 / COM3 / COM4, RJ-45 to DB9 cable optional
UPS Port	Yes, battery optional
Standard USB Port	5 (2 x USB 3.0/2.0 + 3 x USB 2.0)
CR Port	1, control 2 CR
VGA Port	D-USB, 15pins, with 12V support for Posiflex monitor
CR Port	1, control 2 CR via optional Y-cable
Mini-PCle slot	YES
Display & Touch	
LCD	15" TFT LCD
Resolution	1024 x 768
Touch	Bezel-free Projected Capacitive Touch (IPG5 on front panel)
B	
Physical Dimension	070, 000, 050,7
Dimension (W x D x H in mm)	372 x 320 x 252.7
Weight (N.W. in Kg)	6.2
Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
3	<u> </u>
Options	
SSD	2.5" SSD
SA-105	Side Attachment for XT Series with 3 track MSR
SA-205	Side Attachment for XT Series with iButton
SA-305	Side Attachment for XT Series with support for 3 track MSR, RFID and Finger Print Sensor
SA-405	Side Attachment for XT Series with support for 3 track MSR, 3G dongle and Finger Print Sensor
LM-3010	9.7" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-3014	14" 1366 x 768 rear-mount wide screen 2nd display for XT Series (VGA interface)
LM-3015	15" 1024 x 768 rear-mount 2nd display for XT Series (VGA interface)
LM-6607	7" 800 x 480 rear-mount 2nd display for XT series (USB interface)
PD-2608UE	2 x 20 VFD, rear-mount, USB with Virtual COM support
PD-350UE	2 x 20 LCD, rear-mount, USB with Virtual COM support
PD-6607	7" color LCD graphical line display, rear-mount (USB interface)
WIFI	External USB dongle or internal mini-PCle module
****	Executed COS deligio di ilicatici milita dio modulo

^{*} The product information and specifications are subject to change without prior notice. * Please refer to the web site for more attachment options.













High End POS Terminal

Design and Manufacturing in Taiwan by Posiflex Technology Inc.

The product information and specifications are subject to change without prior notice.



POSIFLEX TECHNOLOGY INC.

No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan Tel: +886-2-2299-1599 E-mail: sales@posiflex.com.tw

Fax: +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller









In today's retail and hospitality market, POS terminal is no longer just a cold and hard business tool. It is a part of the store decoration, a part of the store image. Each curve and detail of the POS terminal should add something to the overall mood of the store, to lift the shopping experience of the customers.

With a bezel free touch screen, beautifully sculptured slim body, sexily curved base stand, Posiflex XT-4015 looks right at home at any elegantly decorated store. And more than just good looks, XT-4015 can be equipped with the lighting fast Intel Core i7 CPU that provides ample muscle power to handle any task imaginable.



LOOKS

XT Series is the first to come from new Posiflex design language. Slimmer and sexier than ever, it is a sharp departure from the traditionally more conservative Posiflex terminal design. Every curves and details are carefully thought out to make XT Series one of the most visually desirable terminals in the market.

Flexibility

XT series comes with the selection of two foldable bases, the curvy slim GEN7E Base and the larger but practical GEN8E Base. [U.S Patent 9004436]

The new foldable base allows XT Series to be configured into different configurations. "Flat Folded Mode" to save the shipping package volume. "Low Profile Mode" to allow greater interaction between cashier and the customers; and the traditional "Full Extended Mode". All this can be achieved with a simple pull of the hidden lever. This one terminal/multi-configurations concept provides unmatched flexibility to store owners and system integrators alike.



Full Extended Mode



Low Profile Mode



With 2nd LCD display



Dual LAN
XT-4015 p



at it without even breaking a sweat.

XT Series offers a wide range of performances, with

XT-4015 that stands out above everything else. In its

heart beats an Intel Core i7 3.9GHz CPU (optional)

that is powerful enough to process anything throw



GEN8E Base

Performance

Optional GEN8E Base that integrates internal power adaptor and PoweredUSB port into the base stand, which allows for clutter free counter.